



The bipolar electrolytic capacitors of the **ECap AC · Audio Coupling & Signal Cap PLAIN** series are made of smooth and thus low-loss foils. This has a positive effect on the sound characteristics. Music is reproduced in more details and nuances. Highlights:

Capacity range	1µF to 200µF
Electric strength	AC23 DC35 · AC35 DC50 · AC50 DC70
Temperature range	-40°C/-40°F to 85°C/+185°F
Service life [U _R · I _R]	5,000 hours at +85°C/+185°F
Loss angle [tan α]	0.025 @ 1kHz

ECAP70 (formerly Bg50)

Electrolytic capacitors 70 VDC / 50 VAC, plain

Capacity [µF] ±5%	Body Ø * L [mm]	Wire Ø * L [mm]	[€]
1.0	10 * 20	0,8 * 60	
1.5	10 * 20	0,8 * 60	
2.2	10 * 30	0,8 * 60	
2.7	10 * 30	0,8 * 60	
3.3	10 * 30	0,8 * 60	
3.9	10 * 30	0,8 * 60	
4.7	10 * 30	0,8 * 60	
5.6	12 * 30	0,8 * 60	
6.8	12 * 30	0,8 * 60	
8.2	14 * 37	0,8 * 60	
10	14 * 37	0,8 * 60	
15	18 * 39	0,8 * 60	
22	25 * 38	0,8 * 60	
33	25 * 38	0,8 * 60	
47	25 * 49	0,8 * 60	

ECAP50 (formerly Bg35)

Electrolytic capacitors 50 VDC / 35 VAC, plain

Capacity [µF] ±5%	Body Ø * L [mm]	Wire Ø * L [mm]	[€]
47	25 * 38	0,8 * 60	
56	25 * 49	0,8 * 60	
68	25 * 49	0,8 * 60	
82	30 * 50	0,8 * 60	
100	30 * 50	0,8 * 60	