

## Power Capacitors MLytic AG

30! Years Inner Excellence

The **MLytic® AG • Audio Grade Power Cap** series is especially engineered for use in small power and pre amplifiers.

**MLGO • glue-on** capacitors offer non-magnetic, straight, tinned copper wires  $\varnothing$  1.2mm  $\approx$  AWG17. Additionally they own a vibration-reducing, traction-relieving, self-adhesive MPSA • Mounting Pad.

They supersede the well-known MLSI series. Drill hole spacing [pitch] of **MLGO • glue-on** remains 10mm/0.39inch. Hence they are snap-in capacitor intermateable and so particularly suitable for repairs and modifications.



### MLGO

#### Audio Grade Power Cap, Glue-On, 2Pin

Rated Voltage [VDC]	Capacitance [ $\mu$ F] $\pm$ 20%	Case Size $\varnothing$ * L [mm]	Wire Size $\varnothing$ * L [mm]	Rated Ripple Current IR~ at Tmax and 100Hz [A]	Surge Voltage [VDC]	ESR at 100 Hz [mOhm]	Tan $\delta$ @ 100Hz	Nominal Current IR for 5 Min. [ $\mu$ A]	[€]
100	1000	25 * 30	1,2 * 9	1,2	115	127	8	600	10,90
100	1500	25 * 35	1,2 * 9	1,5	115	85	8	900	11,90
80	10000	35 * 50	1,2 * 9	3,9	92	24	15	4800	25,90
63	2200	25 * 30	1,2 * 9	1,7	72	58	8	830	10,90
63	3300	30 * 30	1,2 * 9	2,1	72	48	10	1246	11,90
63	4700	30 * 35	1,2 * 9	2,6	72	41	12	1776	13,90
63	6800	30 * 40	1,2 * 9	3,0	72	28	12	2570	15,90
63	8200	30 * 45	1,2 * 9	3,4	72	23	12	3100	17,90
63	10000	30 * 50	1,2 * 9	3,5	72	24	15	3780	19,90
63	15000	35 * 60	1,2 * 9	5,1	72	16	15	5670	24,90
63	22000	35 * 70	1,2 * 9	6,0	72	13	18	8316	34,90
40	4700	25 * 30	1,2 * 9	1,8	46	51	15	1128	10,90
40	6800	25 * 35	1,2 * 9	2,1	46	42	18	1632	12,90
40	10000	30 * 40	1,2 * 9	2,7	46	35	22	2400	14,90
40	22000	35 * 50	1,2 * 9	4,4	46	18	25	5280	24,90
40	33000	35 * 60	1,2 * 9	5,3	46	14	30	7920	29,90
25	10000	25 * 35	1,2 * 9	2,4	28	32	20	1500	11,90
25	22000	30 * 40	1,2 * 9	3,5	29	20	28	3300	17,90
25	47000	35 * 50	1,2 * 9	5,9	29	10	30	7050	24,90